

Description	Bonding Agent	Injection Resin	Chemical Anchoring	Low Temperature Anchoring	Crack Healer/Sealer	Crack Repair	Control Joint Sealant	Epoxy Grout	Machine Chock	Bonder / Rebar Primer	Low Temp. Repairs	Interior and Exterior Repairs	Epoxy Mortar
Sure Seal LV/LM													
Sure Inject J56													
Sure Inject J56 SLV													
Sure Bond J58													
Sure Anchor J50													
Sure Anchor I J51													
All Weather J51AW													
Epoxy Grout J55													
Poxy Chock													
Sure Patch													
Rapid Resin Repair													
Perma Prime 3C													
Sure Fil J52													

Blue cell indicates that the description or specification applies to the product.

Description	Gel Paste	Medium Viscosity	Low Viscosity	Type I, II, IV, V	Type I, II, IV	Type I, IV	Type III	Grade 1	Grade 2	Grade 3	Class A, B, C	Class B, C
Sure Seal LV/LM												
Sure Inject J56												
Sure Inject J56 SLV												
Sure Bond J58												
Sure Anchor J50												
Sure Anchor I J51											*	
All Weather J51 AW											*	
Epoxy Grout J55												
Sure Patch												

Blue cell indicates that the description or specification applies to the product.

* Except for minimum gel time due to fast set.

ASTM C-881 and AASHTO M-235

- Type I** Non load bearing, bond hard to hard
- Type II** Non load bearing, bond hard to fresh
- Type III** Skid resistant overlays, exterior mortar patching
- Type IV** Load bearing, bond hardened to hardened concrete
- Type V** Load bearing, bond hard to fresh

- Grade 1** Low Viscosity
- Grade 2** Medium Viscosity
- Grade 3** High Viscosity Gel

- Class A** Application Temp. < 40°F
- Class B** Application Temp. 40 - 60 °F
- Class C** Application Temp. 60°F and above